



## Lifting Eye Starpoint RUD VRS-F

### Product information

Star shaped design, can be adjusted to the direction of pull. Higher load capacities than DIN 580-Eyebolts

**Material:** Forged high tensile engineering steel, crack detekted.

**Marking:** According to standard, WLL

**Finish:** Striking fluorescent pink powder coating

**Standard:** EN 1677-1

**Safety factor:** 4:1

Part Code	Code	WLL ton	Thread mm	Thread	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	N mm	T mm	Weight kg	Delivery time
421100010262	VRS-F	0.1	M6	M6	15	13	35	36	40	23.5	65	24	10	49	0.07	3
421100030260	VRS-F	0.3	M8	M8	11	9	25	25	30	16.3	47	12	6	35	0.12	3
421100040260	VRS-F	0.4	M10	M10	11	9	25	25	30	16.3	47	15	6	35	0.12	3
421100080260	VRS-F	0.75	M12	M12	13	10	30	30	34	19.8	56	18	8	42	0.21	3
421100080267	VRS-F	0.75	M14	M14	13	10	30	30	34	19.8	56	18	8	42	0.22	3
421100150265	VRS-F	1.5	M18	M18	15	13	35	36	40	23.5	65	24	10	49	0.39	3
421100230260	VRS-F	2.3	M20	M20	17	16	40	41	50	-	76	30	12	58	0.6	3
421100320260	VRS-F	3.2	M24	M24	20	19	49	51	60	35	92	36	14	70	1.05	3
421100320266	VRS-F	3.2	M27	M27	20	19	49	51	60	35	92	36	M27	70	1.18	7
421100450260	VRS-F	4.5	M30	M30	26	24	60	66	75	44	114	45	17	87	2.08	3
421100700260	VRS-F	7	M36	M36	32	29	73	76	98	53	135	54	22	104	3.49	7
421100900260	VRS-F	9	M42	M42	37	33	84	86	111	62	158	63	24	121	5.4	3
421100900268	VRS-F	9	M42	-	37	33	84	86	111	62	158	63	24	121	5.4	7
421101200260	VRS-F	12	M48	M48	42	42	94	100	128	70	180	72	27	138	8.17	7
421102000260	VRS-F	20	M64	-	55	49	120	121	158	90	229	96	36	177	17.79	7

# Blueprint

