


ROPETEX PERFORM 35C

Product information

ROPETEX



ROPETEX PERFORM 35C is a flexible high-quality rotation resistant steel wire rope. The strands are compacted giving it a high breaking load and making it wear resistant. ROPETEX PERFORM 35C is very well suited for multi-layer spooling.

Key product benefits

- Rotation resistant steel wire rope
- Excellent lifetime
- Suitable for multi-layer drum spooling
- Very resistant against crushing
- Very wear resistant
- High breaking load (MBL)

Main applications

- Hoist ropes
- Auxiliary hoist ropes

Standard: EN12385

Rope Category Number acc. to ISO4309:2017: 23-2

Rope construction: 35xK7WS

Marking: According to standard

Temperature range: -40°C up to +60°C with standard lubricant, wider range on request

Standard: EN 12385-4

Fill factor: 0,72

RCN: 23-2

Tolerance Ø: +2% to +4%

Tower crane



Truck crane



Mobile port crane



Mobile port crane



Offshore crane



Offshore crane



Crawler crane



Crawler crane



Luffing crane



Self-erected crane



Piling crane



Truck crane



Offshore crane



Deck crane



Knuckle boom crane



Winch rope



Part Code	Rope Diameter,	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
104100806270012	8	1,960	-	-	Galvanized	-	-
104100906270012	9	1,960	-	-	Galvanized	-	-
104101006270012	10	1,960	-	-	Galvanized	-	-
104101106270012	11	1,960	-	-	Galvanized	-	-
104101206270012	12	1,960	-	-	Galvanized	-	-
104101306270012	13	1,960	-	-	Galvanized	-	-
104101406270012	14	1,960	-	-	Galvanized	-	-
104101506270012	15	1,960	-	-	Galvanized	-	-
104101606270012	16	1,960	-	-	Galvanized	-	-
104101806270012	18	1,960	-	-	Galvanized	-	-
104102006270012	20	1,960	-	-	Galvanized	-	-
104102206270012	22	1,960	-	-	Galvanized	-	-
104102506270012	25	1,960	-	-	Galvanized	-	-
104102606270012	26	1,960	-	-	Galvanized	-	-