

Ferrule T Talurit®



Product information

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for fibre core single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and spiral strand ropes.

Material: Aluminum

Marking: According to standard

Standard: EN 13411-3

except size range

Note: See the manufacturer's product data sheet in the tab "Documents" for guidance on dimension selection.

Part Code	Ferrule size mm	Length mm	Delivery time
120100300020	3	14	3
120100350020	3.5	16	3
120100400020	4	18	3
120100450020	4.5	20	3
120100500020	5	23	3
120100600020	6	27	3
120100650020	6.5	29	3

120100700020	7	32	3
120100800020	8	36	3
120100900020	9	40	3
120101000020	10	45	3
120101100020	11	50	3
120101200020	12	54	3
120101300020	13	59	3
120101400020	14	63	3
120101600020	16	72	3
120101800020	18	81	3
120102000020	20	90	3
120102200020	22	99	3
120102400020	24	108	3
120102600020	26	117	3
120102800020	28	126	3
120103000020	30	135	3
120103200020	32	144	3
120103400020	34	153	3
120103600020	36	162	3
120103800020	38	171	3
120104000020	40	180	3
120104400020	44	198	3
120100100020	1	6.5	3

120100200020	2	9	3
120104200020	42	189	3
120104600020	46	207	3
120105000020	50	225	3
120105400020	54	243	3