

Chain SA/S - EN818-2 Gr. 10

Product information



General: Chain for lifting or lashing (other safety factor). Available in 2 different qualities

Star Alloy (SA/S):

- Working temperature: max. 200°C
- Grade Marking: "10" on link every 300mm (up to 16mm) others every 900 mm.
- Surface: Purple varnished

Star Alloy Plus+ (SAP/S): for working temperatures up to 380°C (Available on request)

Material: Alloy steel.

Marking: According to standard

Temperature range: Star Alloy SA/S: -40°C up to 200°C - Star Alloy Plus+ SAP/S: -40°C up to 380°C

Standard: EN 818-2

higher capacity

Warning: Not to be heat treated.

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | Min. Breaking force, kN | Pitch Length | D mm | P mm | Li min. | Le max. | Weight kg/m | Delivery time |
|-----------------|----------------------|------------|----------------------------|--------------|---------|---------|---------|---------|----------------|---------------|
| 203501000000050 | 10 | 4 | 157 | 30 | 10 | 30 | 13.5 | 36 | 2.46 | 3 |
| 203501300000050 | 13 | 6.7 | 265 | 39 | 13 | 39 | 17.5 | 47 | 4.18 | 3 |
| 203501600000050 | 16 | 10 | 402 | 48 | 16 | 48 | 21.5 | 58 | 6.28 | 3 |

Blueprint

