



Steel Wire Rope 35x7 (Rotation resistant)

Product information



Typical applications: Hoist rope for tower cranes, mobile cranes, electrical hoists and other applications where rotation resistant rope is required.

ISO 4309 Rope Category No: All Diameters **RCN.23-2**

Rope construction: Rotation resistant, made out of conventional strands.

Marking: According to standard

Standard: EN 12385-4

Fill factor: 0.61

RCN: 23-2

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
102100804270071	8	1,960	-	-	Galvanized	-	-
102100904270071	9	1,960	-	-	Galvanized	-	-
102101004270071	10	1,960	-	-	Galvanized	-	-
102101204270071	12	1,960	-	-	Galvanized	-	-
102101304270071	13	1,960	-	-	Galvanized	-	-
102101404270071	14	1,960	-	-	Galvanized	-	-
102101504270071	15	1,960	-	-	Galvanized	-	-
102101604270071	16	1,960	-	-	Galvanized	-	-
102101804270071	18	1,960	-	-	Galvanized	-	-
102101904270071	19	1,960	-	-	Galvanized	-	-
102102004270071	20	1,960	-	-	Galvanized	-	-
102102204270071	22	1,960	-	-	Galvanized	-	-
102102404270071	24	1,960	-	-	Galvanized	-	-