



Wire rope Dyform 34LR-PI

Product information



Very Low Rotation.

Superior bending fatigue life when compared with conventional low rotation ropes.

Excellent resistance to crushing and abrasion particularly on multi layer drums resulting from the compacted strands.

Reduced elongation results from increased steel content and the Dyform process.

Plastic impregnation to further extend fatigue life, improve structural stability and resistance to corrosion.

ISO 4309 Rope Category No: 10-40mm **RCN.23-2**, 42-76mm **RCN.31**

Features: Extremely strong low rotation Crane Hoist Rope.

Material: High Carbon Steel

Marking: According to standard, CE-marked, On Termination ID

Finish: Galvanized or Ungalvanized

Standard: EN 12385-4

Fill factor: 0.76

RCN: 23-2

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
104101006270059	10	1,960	-	Galvanized	-	-
104101106270059	11	1,960	-	Galvanized	-	-
104101206270059	12	1,960	-	Galvanized	-	-
104101306270059	13	1,960	-	Galvanized	-	-

104101406270059	14	1,960	-	Galvanized	-	-
104101506270059	15	1,960	-	Galvanized	-	-
104101606270059	16	1,960	-	Galvanized	-	-
104101706270059	17	1,960	-	Galvanized	-	-
104101806270059	18	1,960	-	Galvanized	-	-
104101906270059	19	1,960	-	Galvanized	-	-
104102006270059	20	1,960	-	Galvanized	-	-
104102106270059	21	1,960	-	Galvanized	-	-
104102206270059	22	1,960	-	Galvanized	-	-
104102306270059	23	1,960	-	Galvanized	-	-
104102406270059	24	1,960	-	Galvanized	-	-
104102506270059	25	1,960	-	Galvanized	-	-
104102606270059	26	1,960	-	Galvanized	-	-
104102806270059	28	1,960	-	Galvanized	-	-
104103006270059	30	1,960	-	Galvanized	-	-
104103206270059	32	1,960	-	Galvanized	-	-
104103406270059	34	1,960	-	Galvanized	-	-
104103506270059	35	1,960	-	Galvanized	-	-
104103606270059	36	1,960	-	Galvanized	-	-
104103806270059	38	1,960	-	Galvanized	-	-
104104006270059	40	1,960	-	Galvanized	-	-
104104206270059	42	1,960	-	Galvanized	-	-
104104406270059	44	1,960	-	Galvanized	-	-

104104606270059	46	1,960	-	Galvanized	-	-
104104806270059	48	1,960	-	Galvanized	-	-
104105006270059	50	1,960	-	Galvanized	-	-