

## Steel Wire Rope 6x19M-FC

### Product information



Steel wire rope for cranes, hoists, and slings.

**ISO 4309 Rope Category No:** All Diameters **RCN.04**

**Rope construction:** 6x19M-FC

**Marking:** According to standard

**Standard:** EN 12385-4


**Fill factor:** 0.45

**RCN:** 04

Slings



Overhead cranes



Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay.	Min. Breaking force, kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
101100304250190	3	1,770	Galvanized	sZ	4.89	3.21	Dry	3.1
101100404250190	4	1,770	Galvanized	sZ	8.69	5.71	Dry	5.5
101100504250190	5	1,770	Galvanized	sZ	13.6	8.93	Dry	8.7
101100604250190	6	1,770	Galvanized	sZ	19.6	12.9	Dry	13
101100704250190	7	1,770	Galvanized	sZ	26.6	17.5	Dry	17
101100804250190	8	1,770	Galvanized	sZ	34.8	22.8	Dry	22.1
101101004250190	10	1,770	Galvanized	sZ	54.3	35.7	Dry	34.6