



## Lifting Eye RUD VRS-F Starpoint, UNC thread

### Product information

- 360° adjustable in force direction
- several times higher WLL than the DIN 580 eye bolt
- Easy-Fit-Key for easy assembly and disassembly

**Marking:** CE-marked

**Safety factor:** 4:1

Part Code	WLL ton	Thread Inch	B mm	C mm	D mm	E mm	G mm	I mm	K mm	L mm	N mm	T mm	Weight kg	Delivery time
421100040740	0.4	3/8 -16	11	9	25	25	30	16.3	47	15	6.35	35	0.12	3
421100040745	0.4	7/16 -14	11	9	25	25	30	16.3	47	15	6.35	35	0.12	3
421100080740	0.75	1/2 -13	13	10	30	30	34	19.8	56	19	7.94	42	0.22	3
421100150740	1.5	5/8 -11	15	13	35	36	40	23.5	65	24	9.53	49	0.33	3
421100230740	2.3	3/4 -10	17	16	40	41	50	29.3	76	29	12.7	58	0.58	3
421100230745	2.3	7/8 -9	17	16	40	41	50	29.3	76	33	12.7	58	0.61	3
421100320745	3.2	1-1/8"-7	20	19	49	51	60	35	92	36	9/16"	70	1	7
421100320746	3.2	1-1/8"-8	20	19	49	51	60	35	92	36	9/16"	70	1	7

## Blueprint

