



Eye Sling Hook X-044/S

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2,5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-2

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | A mm | D mm | H mm | K mm | P1 mm | T mm | Weight kg | Delivery time |
|--------------|-------------------|---------|------|------|------|------|-------|------|-----------|---------------|
| 402300140010 | 6 | 1.4 | 20 | 10 | 19 | 80 | 23 | 17 | 0.3 | 3 |
| 402300250010 | 7-8 | 2.5 | 25 | 12 | 22 | 98 | 28 | 20 | 0.5 | 3 |
| 402300400010 | 10 | 4 | 33 | 15 | 30 | 122 | 36 | 23 | 1 | 3 |
| 402300670010 | 13 | 6.7 | 40 | 18 | 38 | 152 | 40 | 28 | 1.8 | 3 |
| 402301000010 | 16 | 10 | 51 | 22 | 44 | 185 | 44 | 36 | 3.4 | 3 |
| 402301600010 | 20 | 16 | 61 | 27 | 64 | 230 | 54 | 48 | 7.3 | 3 |
| 402301900010 | 22 | 19 | 51 | 31 | 61 | 245 | 76 | 52 | 9.3 | 3 |
| 402302650010 | 26 | 26.5 | 65 | 34 | 77 | 285 | 77 | 61 | 13.5 | 7 |
| 402304000010 | 32 | 40 | 91 | 41 | 79 | 358 | 114 | 65 | 22 | 7 |

Blueprint

