



Swivel Self Locking Hook X-027N

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Rotate when loaded.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Built with ball bearing and enables full swivel feature under load.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard

Temperature range: Tempering temperature minimum 400°C .

Finish: Blue painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | EWL mm | A mm | B mm | D mm | H mm | K mm | P mm | T mm | Weight kg | Delivery time |
|--------------|-------------------|---------|--------|------|------|------|------|------|------|------|-----------|---------------|
| 420500140950 | 6 | 1.4 | 149 | 32 | 23 | 12 | 19 | 149 | 28 | 15 | 0.7 | 3 |
| 420500250950 | 7-8 | 2.5 | 186 | 36 | 29 | 13 | 24 | 186 | 34 | 20 | 1.2 | 3 |
| 420500400950 | 10 | 4 | 218 | 41 | 35 | 16 | 30 | 218 | 44 | 26 | 2 | 3 |
| 420500670950 | 13 | 6.7 | 276 | 46 | 44 | 21 | 39 | 276 | 51 | 30 | 4.1 | 3 |
| 420501000950 | 16 | 10 | 329 | 61 | 50 | 23 | 49 | 329 | 60 | 36 | 7.2 | 3 |
| 420501600950 | 20 | 16 | 387 | 74 | 82 | 25 | 65 | 403 | 70 | 53 | 13 | 3 |
| 420501900950 | 22 | 19 | 457 | 97 | 96 | 33 | 63 | 454 | 80 | 49 | 20 | 7 |
| 420502650950 | 26 | 26.5 | 535 | 123 | 116 | 51 | 69 | 535 | 99 | 56 | 33 | 7 |

Blueprint

