



Ring Clutch Starcon

Product information

The ring clutch is used for lifting and transport of the transport anchor system STA (Transport Anchors STA-S, STA-Z, STA-SA, STA-SE, Sandwich Panel Anchor STA-ST, Plate Anchor STA-P or Flat Foot Anchor STA-F). Load of the ring clutch can be made from all directions. The head of the coupling incorporates with a locking bolt which is attached to the anchor.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Material: Steel

Marking: CE-marked, UKCA-marked, Batch code, Load group, WLL, Starcon

Finish: Electro galvanized

Safety factor: 4:1

| Part Code | WLL ton | Load grp. | a mm | b mm | c mm | d mm | L mm | t mm | Weight | Delivery time |
|--------------|---------|-----------|------|------|------|------|------|------|--------|---------------|
| 650290025001 | 2.5 | 2.5 t | 70 | 58 | 80 | 27 | 265 | 12 | 0.95 | 3 |
| 650290050001 | 5 | 5 t | 86 | 65 | 105 | 36 | 330 | 16 | 1.5 | 3 |
| 650290100001 | 10 | 10 t | 112 | 90 | 150 | 50 | 425 | 25 | 3.18 | 3 |

Blueprint

