



Master Link Assembly

Product information

For 3-and 4 leg slings.

Material: Quenched and tempered alloy steel grade 8.

Marking: Code and grade.

Finish: Painted.

Warning: Not to be heat treated.

Safety factor: 5:1

Grade: 8

Part Code	WLL ton	Dim./Type	Master link Type	Master link Dim.	Intermediate M.L Type	Intermediate M.L Dim.	Weight kg	Delivery time
401100410090	4.1	Q.16.B	16.B.6	70x120	13.B.5	51x95	1.2	3
401100650090	6.5	Q.20.B	20.B.7	90x170	16.B.6	70x120	2.5	3
401100820090	8.2	Q.22.B	22.B.8	90x170	20.B.6	80x150	3.8	3
401101070090	10.7	Q.25.B	25.B.6	100x190	20.B.6	80x150	4.5	3
401101290090	12.9	Q.28.B	28.B.6	113.5x209	22.B.6	90x170	6.4	3
401101710090	17.1	Q.32.B	32.B.6	140x270	25.B.6	100x190	9.9	3
401102810090	28.1	Q.38.B	38.B.6	140x270	32.B.6	140x270	18.2	3
401103830090	38.3	Q.45.B	45.B.6	170x320	38.B.6	140x270	27.7	3
401104500090	45	Q.50.B	50.B.6	200x380	38.B.6	200x380	33.2	3
401106530090	65.3	Q.60.B	60.B.6	220x430	50.B.6	200x380	66	3
401108400090	84	Q.70.B	70.B.6	250x500	60.B.6	220x430	103	7