



Polyethylene Rope, 3-Strand

Product information

Rope made of polyeten for applications like mooring, commercial fishing and industrial needs.

Design: 3 strand.

Specific gravity: 0.93(floats).

Melting point: Apx. 130 °C.

Elongation: Apx. 18%.

Material: Polyeten. It is a smooth rope, resistant to rot and it has a relatively high elongation.

Finish: Orange.

| Part Code | Diameter mm | Min. Breaking force, kN | MBL | Rope ends | Weight kg/110m | Delivery time |
|-----------------|-------------|-------------------------|-----|------------|----------------|---------------|
| 300300600000040 | 6 | 3.9 | 0.4 | Plain ends | 3.6 | 3 |
| 300300800000040 | 8 | 6.8 | 0.7 | Plain ends | 5.2 | 3 |
| 300301000000040 | 10 | 10.7 | 1.1 | Plain ends | 5.4 | 3 |
| 300301200000040 | 12 | 15.6 | 1.6 | Plain ends | 7.9 | 3 |
| 300301400000040 | 14 | 20.6 | 2.1 | Plain ends | 10.5 | 3 |
| 300301600000040 | 16 | 27.4 | 2.8 | Plain ends | 14.1 | 3 |
| 300301800000040 | 18 | 34.3 | 3.5 | Plain ends | 17.7 | 3 |
| 300302000000040 | 20 | 42.1 | 4.3 | Plain ends | 22 | 3 |
| 300302200000040 | 22 | 50 | 5.1 | Plain ends | 26.7 | 3 |
| 300302400000040 | 24 | 59.8 | 6.1 | Plain ends | 32.5 | 3 |
| 300302800000040 | 28 | 80.4 | 8.2 | Plain ends | 43.2 | 3 |