

Lifting Eye RUD ACP-TURNADO



Product information



- Unique RUD spring mechanism
- No stopping of the lifting bale
- No dangerous transverse loads - no worst case
- Integrated RFID transponder to make checks easier
- Wear lenses for checking discard criteria

According to the EC-Machinery Directive 2006/42/EC

Marking: According to standard

Temperature range: -40°C up to +100°C.

Standard: EN 1677-1, EN ISO 12100

Safety factor: 4:1

Part Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	K mm	L mm	M mm	N mm	T mm	Weight kg	Delivery time
42157912061	0.7	-	11	10.5	38	30	12	28	45	13	58	40	M8	5	83	0.36	7
42157911052	12.5	106	32	32	82	70	45	60	128	55	168	105	M36	22	189	7.1	7
42157911053	16	106	32	32	82	70	53	60	136	65	168	113	M42	24	189	7.5	7
42157912630	20	127	45	45	103	90	61	78.5	169	75	204	139	M48	24	235	16.04	7
42157912631	24	123.5	45	45	103	95	65	108	173	75	204	145	M52	24	232	16.34	3
42157912632	27	123.5	45	45	103	95	70	108	178	75	204	150	M56	24	232	16.5	7
42157912633	32.5	123.5	45	45	103	95	80	108	188	75	204	-	M64	24	232	17.19	7

Blueprint

