

Weld-on Point TAPS

Product information

Weld-on lifting attachment point for plane surfaces.

- Compact design
- Secured four times against breakage
- Weld-on shackle made of material S355JR according to EN 10025
- Also loadable transversely to the swivel direction

Features: 180° swing

Material: Eye of alloy steel. Welding attachment of steel St 52

Marking: CE-marked, WLL

Finish: Painted







Note: The surface that the lifting eyes shall be attached to shall be flat and tolerate the load it is going to be exposed to

Safety factor: 4:1

Grade: 8

Part Code	Code	WLL ton	a mm	b mm	c mm	Ø d	e mm	f mm	l mm	Weight kg	Delivery time
42150381701000	TAPS 1	1.12	35	64	35	13	26	70	40	0.35	3
42150381702000	TAPS 2	2	37	66	36	13	27	70	41	0.36	3
42150381703000	TAPS 3	3.15	49	92	50	18	37	92	53	0.84	3
42150381705000	TAPS 5	5.3	60	111	60	22	45	111	63	1.6	3
42150381708000	TAPS 8	8	75	132	70	26	50	127	68	2.61	3
42150380415000	TAPS 15	15	90	185	100	30	60	190	120	5.4	3

Technical data

Kind of attachment								
Number of pieces	1	1	2	2	2	2	3 o. 4	3 o. 4
Inclination angle	0°	90°	0°	90°	0°-45°	45°-60°	0°-45°	45°-60°
	WLL	WLL	WLL	WLL	WLL	WLL	WLL	WLL
Code	t	t	t	t	t	t	t	t
TAPS 1	1,6	1,12	3,2	2,24	1,5	1,12	2,36	1,6
TAPS 2	3	2	6	4	2,8	2	4,25	3
TAPS 3	4,75	3,15	9,5	6,3	4,25	3,15	6,3	4,75
TAPS 5	8	5,3	16	10,6	7,1	5,3	11,2	8
TAPS 8	12	8	24	16	11,2	8	16	12
TAPS 15	22,4	15	45	30	21,2	15	31,5	22,4
TAPS 20	30	20	60	40	30	20	40	30
TAPS 25	37,5	25	75	50	33,5	25	50	37,5
TAPS 30	45	30	90	60	45	30	63	45

TAPS 35	50	35	100	70	47,5	35	70	52,2
TAPS 40	60	40	120	80	56	40	80	60
TAPS 50	71	50	142	100	70	50	106	75
TAPS 63	75	63	150	126	90	63	133	95

Blueprint

