



Kiswire Neptune N2 Hyrope 35xK7

Product information



- Rotation poor
- Anointed
- High breaking strength
- Compact
- Large contact surface

Rope construction: 35xK7

Marking: According to standard

Standard: EN 12385

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force, kN	Steel area mm ²	Lubrication	Weight kg/100m
109802506270369	25	1,960	Galvanized	zZ	560	340	SupplierStandard	306
109802806270369	28	1,960	Galvanized	zZ	721	423	SupplierStandard	384
109803406270369	34	1,960	Galvanized	zZ	1,103	620	SupplierStandard	566.2
109803404270369	34	1,960	Galvanized	sZ	1,103	620	SupplierStandard	566.2
109804006270369	40	1,960	Galvanized	zZ	1,527	865	SupplierStandard	784
109804804270369	48	1,960	Galvanized	sZ	2,140	1,240	SupplierStandard	1,130
109805404270369	54	1,960	Galvanized	sZ	2,660.5	1,580	SupplierStandard	1,460
109805604270369	56	1,960	Galvanized	sZ	2,870	1,690	SupplierStandard	1,570
109805606270369	56	1,960	Galvanized	zZ	2,870	1,690	SupplierStandard	2,440
109806206270369	62	1,960	Galvanized	zZ	3,630	2,000	SupplierStandard	1,940
109806404270369	64	1,960	Galvanized	sZ	3,792	2,210	SupplierStandard	2,020
109806406270369	64	1,960	Galvanized	zZ	3,792	2,210	SupplierStandard	2,020
109806606300369	66	2,160	Galvanized	zZ	3,920	2,350	SupplierStandard	2,150
109807006270369	70	1,960	Galvanized	zZ	4,400	2,640	SupplierStandard	2,440
109807004270369	70	1,960	Galvanized	sZ	4,410	2,640	SupplierStandard	2,440
109807606270369	76	1,960	Galvanized	zZ	5,200	3,110	SupplierStandard	2,900
109807806270369	78	1,960	Galvanized	zZ	5,600	3,050	SupplierStandard	2,950
109809006270369	90	1,960	Galvanized	zZ	6,790	4,360	SupplierStandard	3,950