



Metric Swivel Hoist Rings Crosby HR-125M

Product information

Features:

- The Working Load Limit and Recommended Torque value are permanently stamped into each washer.
- Washer is color coded for easy identification: Silver - Metric thread.
- Bolt specification is a Grade 12.9 Alloy socket head cap screw to DIN 912.
- Designed to be used with ferrous workpiece only.
- BOLT SIZE IDENTIFICATION: The size of the bolt will be stated as in the blueprint. Illustration shows meaning of each dimension given.

Safety factor: 5:1

Part Code	Torque Nm	WLL ton 4:1	WLL ton 5:1	A mm	B mm	C mm	D mm	E mm	ØF mm	G mm	H mm	Weight kg	Delivery time
42151016602	10	0.5	0.4	M8x1,25x40	16.9	69.9	24.6	11.8	8.5	47.5	29.9	0.17	3
42151016613	16	0.55	0.45	M10x1,50x40	16.9	69.9	24.6	11.8	8.5	47.5	28.1	0.18	7
42151016624	38	1.3	1.05	M12x1,75x50	16.9	123	49.8	22.3	17.5	85.1	60.4	1.05	7
42151016635	81	2.4	1.9	M16x2,00x60	26.9	123	49.8	22.3	17.5	85.1	56.3	1.11	3
42151016644	136	2.7	2.15	M20x2,50x65	31.9	123	49.8	22.3	17.5	85.1	52.3	1.17	3
42151016668	312	5.25	4.2	M24x3,00x80	32.8	167	75.2	34.7	25.4	124	70.5	3.21	7
42151016679	637	8.75	7	M30x3,50x120	61.7	222	94.2	44.5	30.5	157	102	6.53	7
42151016690	1,005	13.75	11	M36x4,00x150	54	318	120	60.7	44.5	215	142	16.8	3
42151016712	1,350	16.9	13.5	M48x5,00x160	74	318	120	60.7	44.5	215	130	18	3

Blueprint

