



## Rope Van Beelen D12 Dyneema

### Product information

This type of D12 is, together with D12 SK78, the standard for D12.

- D12 SK78 is 12 strand braided as per ISO 10325
- Breaking load wet and dry is equal.
- Standard coating is in Gold or Grey Powercoat.
- **Melting Temperature:** 150 °C
- **Max. elongation:** 4%
- **Spec. gravity:** 0.97

| <b>Part Code</b> | <b>Diameter<br/>mm</b> | <b>MBL</b> | <b>Rope ends</b> | <b>Weight<br/>kg/100m</b> | <b>Delivery time</b> |
|------------------|------------------------|------------|------------------|---------------------------|----------------------|
| 301200400000280  | 4                      | 1.4        | Plain ends       | 1.1                       | 3                    |
| 301200600000280  | 6                      | 3.7        | Plain ends       | 2                         | 3                    |
| 301200800000280  | 8                      | 6          | Plain ends       | 3.6                       | 3                    |
| 301201000000280  | 10                     | 10.4       | Plain ends       | 5.9                       | 3                    |
| 301201200000280  | 12                     | 14         | Plain ends       | 8                         | 3                    |
| 301201400000280  | 14                     | 18         | Plain ends       | 11                        | 7                    |
| 301201600000280  | 16                     | 24         | Plain ends       | 14                        | 3                    |
| 301201800000280  | 18                     | 30         | Plain ends       | 18                        | 3                    |
| 301202000000280  | 20                     | 38         | Plain ends       | 22                        | 3                    |
| 301202400000280  | 24                     | 53         | Plain ends       | 33                        | 3                    |
| 301203000000280  | 30                     | 78         | Plain ends       | 48                        | 3                    |