



## Master Link Assembly MT GrabiQ V2

### Product information

Designed for use with chain, wire or synthetic rope. For 3-leg and 4-leg slings.

**Material:** Alloy Steel

**Marking:** According to standard, Code, grade, chain size, manufacturing ID

**Finish:** Painted

**Standard:** AS 3775, AS 3776

**Standard:** EN 1677-4

(+25% WLL)

**Safety factor:** 5:1

**Grade:** 10

Part Code	Code	WLL ton	L1 mm	L mm	E mm	D mm	I mm	e mm	d mm	Weight kg	Delivery time
402100431200	MT-6-10 GrabiQ V2	4.3	260	140	80	17	120	60	13	1.5	7
402100781200	MT-8-10 GrabiQ V2	7.8	300	160	95	22	140	80	17	3	7
402101201200	MT-10-10 GrabiQ V2	12	435	275	145	28	160	95	22	6.8	7
402102101200	MT-13-10 GrabiQ V2	21	465	275	145	32	190	110	28	10.9	7
402103101200	MT-16-10 GrabiQ V2	31	545	270	140	40	275	145	32	18.4	7
402104801200	MT-20-10 GrabiQ V2	48	610	340	180	45	270	140	40	29.1	7
402106001200	MT-22-10 GrabiQ V2	60	690	350	200	55	340	180	45	46.4	7
402108501200	MT-26-10 GrabiQ V2	85	725	375	210	60	350	200	55	67.6	7
402112501200	MT-32-10 GrabiQ V2	125	825	450	260	80	375	210	60	110.1	7

## Blueprint

