



General use



## Steel Wire Rope PVC-coated 6x7-FC

### Product information



A galvanized rope equipped with a Fibre Core (FC) and has a PVC-coating. It can be used for various applications such as locking rope, signaling devices, etc but not for lifting.

The PVC-coating is UV stabilized which makes it suitable for longterm outdoor use and it is fully compliant with REACH Directive 1907/2006.

**Rope construction:** 6x7-FC

**Marking:** According to standard

**Temperature range:** -30°C up to +70°C

**Finish:** PVC-coated, see table for colour

**Standard:** EN 12385-4

*except from coating*

**Note:** Peel off coating at end when making any end fittings such as clamping ferrules etc.

**Fill factor:** 0,47

Part Code	Rope Diameter,	Inner diameter	Colour	Tensile strength	Min. Breaking force	Steel area	Lubrication	Weight
	mm	mm		N/mm <sup>2</sup>	kN	mm <sup>2</sup>		kg/100m
105130300200070	3	2	transparent	1,770	2.35	1.48	-	1.38
105130400300070	4	3	transparent	1,770	5.29	3.32	-	3.11
105130500400070	5	4	transparent	1,770	9.4	5.9	-	5.54
105130600400070	6	4	transparent	1,770	9.4	5.9	-	5.54
105130800600070	8	6	transparent	1,770	21.2	13.3	-	12.5