



Fibre Rope 3-Strand Movline Plus HBL

Product information

Movline Plus ropes are made from a high tenacity composite fiber extruded on a custom-built extrusion process. This extremely strong bi-polymer and its balanced twisted construction, result on a rope with good wear resistance and exceptional gripping capabilities that are enhanced by the outer fuzzy surface developed in use, also protecting the inner fibers against abrasion.

Advantages:

- High abrasion and wear resistance
- High strength floating line
- No water absorption
- Good UV resistance

Application areas:

- Tie up and Mooring lines
- General deck lines
- Towing lines

Technical Information:

- Specific Gravity: 0,94
- Melting Point: 165°C
- Elongation in % of the breaking load:

25% 6,0%

50% 11,5%

Material: Mixed Polyolefin

Marking: According to standard

Standard: EN ISO 10572

| Part Code | Diameter mm | Min. Breaking force kN. | Length m | Colour | Rope ends | Weight kg/100m | Delivery time |
|-----------------|----------------|----------------------------|-------------|--------|------------|-------------------|---------------|
| 300304802200250 | 48 | 417 | 220 | Green | Plain ends | 104 | 3 |
| 300305602200250 | 56 | 543 | 220 | Green | Plain ends | 142 | 3 |
| 300306002200250 | 60 | 613 | 220 | Green | Plain ends | 163 | 3 |
| 300306402200250 | 64 | 698 | 220 | Green | Plain ends | 186 | 3 |
| 300307202200250 | 72 | 878 | 220 | Green | Plain ends | 235 | 3 |