

Subsea Shackle Crosby G-209R

Product information

Design: Deformation and angle indicators forged on the bow. Fatigue rated.

Material: Forged steel, Quenched & Tempered, with alloy pins.

Marking: According to standard, CE-marked, WLL

Finish: Galvanized and painted fluorescent yellow.

Standard: EN 13889

Safety factor: 5:1



Part Code	WLL ton	Opening mm	Bolt Ø mm	A +/- 6.35 mm	B mm	C mm	H mm	L mm	O mm	P mm	S mm	T mm	Weight kg	Delivery time
420100650290	6.5	36.6	25.4	36.6	25.4	84	148	102	50	58	17	10	1.69	3
420100850290	8.5	42.9	28.7	42.9	28.7	95.5	167	119	50	61	18	10	2.59	3
420100950290	9.5	46	31.8	46	31.8	108	190	131	70	83	18	12	3.77	3
420101200290	12	51.5	35.1	51.5	35.1	119	210	146	70	84	23	12	5.02	3
420101350290	13.5	57	38.1	57	38.1	133	233	162	75	91	23	15	6.65	3
420101700290	17	60.5	41.4	60.5	41.4	146	254	175	75	93	24	15	8.58	3
420102500290	25	73	51	73	51	178	313	225	90	114	29	17.5	14.1	3
420103500290	35	82.5	57	82.5	57	197	348	253	106	132	30	20	21.4	7
420105500290	55	105	70	105	70	267	453	327	120	145	45	25	42.8	3

Blueprint

