



Steel wire rope Diepa X53 (PZ371)

Product information



Diepa X53 is a non-rotation resistant wire rope with compacted outer strands, plastic insert and high breaking force.

Applications: Lifting wire for mobile cranes, deck cranes and container cranes where multiple parts is being used in lower lifting operations, and where right -and left hand lays are being used in at the same time. Winch and digging machines.

Lay: Ordinary Lay with plastic insert.

Total number of wires: 4-14mm 201, 15-43mm 329, 44-65mm 409, 66-100mm 580.

ISO 4309 Rope Category No: 4-14mm **RCN.04**, 15-44mm **RCN.09**, 45-100mm **RCN.13**

Optional: X50 - Ordinary Lay, X55 - Lang Lay, X58 Lang Lay with plastic insert.
From $\varnothing 76$ mm tensile strenght 2160 N/mm² on request

Marking: According to standard

Finish: Galvanized or bright.

Standard: EN 12385-4

Warning: Not to be used with a swivel.

Fill factor: 0.6750

RCN: 04

| Part Code | Rope Diameter, mm | Tensile strength N/mm ² | Min. Breaking force kN. | Finish | Weight kg/100m | Delivery time |
|-----------------|----------------------|---------------------------------------|----------------------------|--------|-------------------|---------------|
| 103100703070189 | 7 | 1,960 | - | Bright | - | - |
| 103100803070189 | 8 | 1,960 | - | Bright | - | - |
| 103100904070189 | 9 | 1,960 | - | Bright | - | - |
| 103101003070189 | 10 | 1,960 | - | Bright | - | - |
| 103101103070189 | 11 | 1,960 | - | Bright | - | - |
| 103101203070189 | 12 | 1,960 | - | Bright | - | - |
| 103101303070189 | 13 | 1,960 | - | Bright | - | - |
| 103101403070189 | 14 | 1,960 | - | Bright | - | - |
| 103101603070189 | 16 | 1,960 | - | Bright | - | - |
| 103102003070189 | 20 | 1,960 | - | Bright | - | - |
| 103102403070189 | 24 | 1,960 | - | Bright | - | - |
| 103102503070189 | 25 | 1,960 | - | Bright | - | - |
| 103102803070189 | 28 | 1,960 | - | Bright | - | - |
| 103103203070189 | 32 | 1,960 | - | Bright | - | - |
| 103103404070189 | 34 | 1,960 | - | Bright | - | - |