



## Steel wire rope Diepa H40 (SKZ8), non-rotation resistant.

### Product information



**General:** Diepa H40 is a non-rotation resistant wire rope with compacted inner and outer strands. The rope has a very high breaking force.

**Applications:** Jib adjusting rope. Jib retaining rope.

**Lay:** Ordinary lay

**Total number of wires:** 4-6mm 95, 7-15mm 262, 16-24mm 319, 25-44mm 347, 45-64mm 427, 65-76mm 487

**ISO 4309 Rope Category No:** 4-6mm **RCN.02**, 7-15mm **RCN.04**, 16-44mm **RCN.09**, 45-76mm **RCN.13**

**Marking:** According to standard

**Finish:** Galvanized or bright.

**Standard:** EN 12385-4

**Warning:** Not to be used with a swivel.

**Fill factor:** 0.7403

**RCN:** 02

Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay.	Min. Breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
103102804070219	28	1,960	Bright	sZ	747	-	SupplierStandard	-
103103004270219	30	1,960	Galvanized	sZ	860	-	SupplierStandard	-
103103204270219	32	1,960	Galvanized	sZ	979	-	SupplierStandard	-
103103203270219	32	1,960	Galvanized	zS	979	-	SupplierStandard	-
103105404270219	54	1,960	Galvanized	sZ	2,768	-	SupplierStandard	-