

Bow Shackle No 855, Gunnebo - Safety Bolt



Product information

Approved according to: DNV 2.7-1

Forging tolerances: +/-5% on inside width/length.

Material: High tensile steel, quenched and tempered, grade 6.

Marking: According to standard, CE-marked

Temperature range: -20°C to 200°C.

Finish: All parts hot dip galvanized, brown painted bolts/pins on top of galv.

Standard: EN 13889, US. FED. SPEC. RR-C-271

Safety factor: 6:1

Part Code	WLL ton	a mm	c mm	d mm	d1 mm	d2 mm	e mm	Weight kg	Delivery time
420100050410	0.5	12	29	1/4" - 6	8	16	20	0.07	3
420100100410	1	16	36	3/8" - 9	11	22	26	0.17	3
420100200410	2	21	47	1/2" - 13	16	33	33	0.42	3
420100330410	3.25	27	60	5/8" - 16	19	40	42	0.7	3
420100480410	4.75	31	71	3/4" - 19	22	48	49	1.2	3
420100650410	6.5	37	84	7/8" - 22	25	52	60	1.7	3
420100850410	8.5	43	95	1" - 25	28	60	68	2.58	3
420100950410	9.5	46	108	1 1/8" - 28	32	64	74	3.4	3
420101200410	12	52	119	1 1/4" - 32	35	72	83	4.8	3
420101350410	13.5	57	132	1 3/8" - 35	38	76	89	7	3
420101700410	17	60	146	1 1/2" - 38	42	84	98	9	3
420102500410	25	74	178	1 3/4" - 45	50	105	127	15	3
420103500410	35	83	197	2" - 50	57	112	138	21	3
420105500410	55	105	260	2 1/2" - 65	70	145	180	39	3

Blueprint

