

## Chain Short Link VIS 200

### Product information



- Manufactured from special analysis alloy steel.
- Quenched and tempered before proof testing.
- Working load limit up to 40 tonnes.
- 25% higher strength than Grade 80.

**Marking:** According to standard, At least every 20th link, or at least one link per meter, is labeled with manufacturer, grade and traceability code.

**Temperature range:** -29°C up to 205°C

**Finish:** Blue painted

**Standard:** EN 818-2

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	Min. Breaking force, kN	Pitch Length	d mm	p mm	w1 mm	w2	Weight	Delivery time
203500600000160	6	1.4	56.5	-	6	18	7.8	22.2	0.83	3
203500800000160	8	2.5	101	-	8	24	10.4	29.6	1.51	3
203501000000160	10	4	157	-	10	30	13	37	2.27	3
203501300000160	13	6.7	265	39	13	39	16.9	48.1	3.9	3
203501600000160	16	10	402	48	16	48	20.8	59.2	5.79	7
203502000000160	20	16	628	60	20	60	26	74	8.9	3
203502200000160	22	19	760	66	22	66	28.6	81.4	11.4	3
203502600000160	26	26.5	1,060	78	26	78	33.8	96.2	16	3
203503200000160	32	40	1,610	96	32	96	41.6	118	24.1	3

## Blueprint

