



Øyebolt M-279, Crosby

Produkt informasjon

- Working load limits shown are for in-line pull.
- Recommended for in-line pull.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.

Materiale: Forged steel - quenched and tempered.

Sikkerhetsfaktor: 4:1

Art. nr.	WLL tonn	Thread mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Vekt kg	Leveringstid (dager)
421100020690	0,2	M6 x 1.0	M6 x 1.0	13	28,7	19,1	47	4,9	13,5	19,6	0,03	7
421100040690	0,4	M8 x 1.25	M8 x 1.25	13	35,1	22,4	54,6	6,4	15	24,1	0,05	7
421100060690	0,64	M10 x 1.5	M10 x 1.5	17	41,1	25,4	64,3	7,9	17,5	26,5	0,07	7
421100100690	1	M12 x 1.75	M12 x 1.75	20,5	49,5	30,2	77,7	9,7	23,1	32,8	0,11	7
421100180690	1,8	M16 x 2.0	M16 x 2.0	27	60,5	35,1	96	12,7	28,7	38,9	0,25	7
421100250690	2,5	M20 x 2.5	M20 x 2.5	30	70	38,1	108	16	35,1	43,4	0,42	7
421100400690	4	M24 x 3.0	M24 x 3.0	36	95,5	51	142	22,4	46	58,4	1,05	7
421100500690	5	M27 x 3.0	M27 x 3.0	69,8	107	57,1	183	24,6	52,3	59,7	1,42	7
421100600690	6	M30 x 3.5	M30 x 3.5	45	114	63,5	171	25,4	58	69,3	1,77	7
421100850690	8,5	M36 x 4.0	M36 x 4.0	54	140	76	207	31,8	70	83,3	3,12	7
421101400690	14	M42 x 4.5	M42 x 4.5	95,2	159	88,9	266	35	76,2	91,4	4,58	7

Måltabell

