



Turnbuckle Jaw - Jaw G-6323, Green Pin®

Produkt informasjon

Turnbuckle jaw/jaw, with safety bolt. Turnbuckles are used for rigging or tensioning wires, ropes, rods etc. They are designed for in-line rigging, tensioning or lashing.

Standard: Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

Certification: A works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request.

Merking: CE-merket

Sikkerhetsfaktor: 5:1

Art. nr.	WLL tonn	Gjenge	Take up inch	a "	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Vekt kg	Leveringstid (dager)
422100050300	0,54	3/8	6	3/8	273	409	304	12	21	7	9	21	0,55	7
422100160305	1,59	5/8	9	5/8	421	622	480	18	32	13	14	33	2,14	3
422100330305	3,27	7/8	18	7/8	713	1 132	790	27	42	19	19	48	6,56	7
422100450306	4,54	1	12	1	598	859	683	31	50	22	20	54	6,96	7
422100970300	9,71	1 1/2	12	1 1/2	675	942	806	52	71	35	28	80	18,5	7
422100970305	9,71	1 1/2	18	1 1/2	825	1 244	956	52	71	35	28	80	19,3	3
422101270300	12,7	1 3/4	18	1 3/4	938	1 316	1 092	60	86	41	33	90	30	7
422101680300	16,8	2	24	2	1 153	1 673	1 338	63	93	50	40	107	50	7
422103400300	34	2 3/4	24	2 3/4	1 348	1 882	1 604	90	110	70	41	158	109	7

Måltabell

