



Ring MT GrabiQ, Gunnebo

Produkt informasjon

Designet for bruk med kjetting, ståtau og syntetiske stropper. For 3 og 4 bein.

Merking: I henhold til standard

Standard: AS 3775, AS 3776

Standard: EN 1677-4

(+25% WLL)

Sikkerhetsfaktor: 5:1

Klasse: 10

| Art. nr. | Kode | WLL tonn | L1 mm | L mm | E mm | D mm | I mm | e mm | d mm | Vekt kg | Leveringstid (dager) |
|--------------|--------------------|-------------|-------|---------|---------|---------|---------|---------|---------|------------|----------------------|
| 402100431200 | MT-6-10 GrabiQ V2 | 4,3 | 260 | 140 | 80 | 17 | 120 | 60 | 13 | 1,5 | 7 |
| 402100781200 | MT-8-10 GrabiQ V2 | 7,8 | 300 | 160 | 95 | 22 | 140 | 80 | 17 | 3 | 7 |
| 402101201200 | MT-10-10 GrabiQ V2 | 12 | 435 | 275 | 145 | 28 | 160 | 95 | 22 | 6,8 | 7 |
| 402102101200 | MT-13-10 GrabiQ V2 | 21 | 465 | 275 | 145 | 32 | 190 | 110 | 28 | 10,9 | 7 |
| 402103101200 | MT-16-10 GrabiQ V2 | 31 | 545 | 270 | 140 | 40 | 275 | 145 | 32 | 18,4 | 7 |
| 402104801200 | MT-20-10 GrabiQ V2 | 48 | 610 | 340 | 180 | 45 | 270 | 140 | 40 | 29,1 | 7 |
| 402106001200 | MT-22-10 GrabiQ V2 | 60 | 690 | 350 | 200 | 55 | 340 | 180 | 45 | 46,4 | 7 |
| 402108501200 | MT-26-10 GrabiQ V2 | 85 | 725 | 375 | 210 | 60 | 350 | 200 | 55 | 67,6 | 7 |
| 402112501200 | MT-32-10 GrabiQ V2 | 125 | 825 | 450 | 260 | 80 | 375 | 210 | 60 | 110,1 | 7 |

Måltabell

