



Ring MT GrabiQ, Gunnebo

Produkt informasjon

Designet for bruk med kjetting, ståtau og syntetiske stropper. For 3 og 4 bein.

Merking: I henhold til standard

Standard: AS 3775, AS 3776

Standard: EN 1677-4

(+25% WLL)

Sikkerhetsfaktor: 5:1

Klasse: 10

Art. nr.	Kode	WLL tonn	L1 mm	L mm	E mm	D mm	I mm	e mm	d mm	Vekt kg	Leveringstid (dager)
402100431200	MT-6-10 GrabiQ V2	4,3	260	140	80	17	120	60	13	1,5	7
402100781200	MT-8-10 GrabiQ V2	7,8	300	160	95	22	140	80	17	3	7
402101201200	MT-10-10 GrabiQ V2	12	435	275	145	28	160	95	22	6,8	7
402102101200	MT-13-10 GrabiQ V2	21	465	275	145	32	190	110	28	10,9	7
402103101200	MT-16-10 GrabiQ V2	31	545	270	140	40	275	145	32	18,4	7
402104801200	MT-20-10 GrabiQ V2	48	610	340	180	45	270	140	40	29,1	7
402106001200	MT-22-10 GrabiQ V2	60	690	350	200	55	340	180	45	46,4	7
402108501200	MT-26-10 GrabiQ V2	85	725	375	210	60	350	200	55	67,6	7
402112501200	MT-32-10 GrabiQ V2	125	825	450	260	80	375	210	60	110,1	7

Måltabell

