

Rustfri gjenget terminal, AISI 316

Produkt informasjon



Generelt: Beslagene presses på ståtauets.

Utførelse: Polert.

Materiale: Rustfri syrefats stål, AISI 316.

Art. nr.	Tau diameter mm	Bruddstyrke MBL tonn	Gjenge	G tråd	D1 mm	D2 mm	L1 mm	L2 mm	L3 mm	KW mm	Vekt kg/100pc	Leveringstid (dager)
1207900306	3	1,2	R*	M6	3,3	6,35	100	38	48	5,0	2	7
1207900406	4	1,2	R*	M6	4,4	7,50	110	45	48	6,0	2,4	7
1207900406	4	1,7	R*	M8	4,4	7,50	117	45	57	6,0	3	7
1207900510	5	2,5	R*	M10	5,3	9,00	130	51	63	7,0	4,5	3
1207900610	6	3,5	R*	M10	6,5	12,58	145	64	63	11	8,4	7
1207900612	6	5,1	R*	M12	6,5	12,58	162	64	80	11	11	7
1207900812	8	5,1	R*	M12	8,4	16,00	185	83	80	14	19,2	3
1207901016	10	9,4	R*	M16	10,5	17,80	210	89	100	15	35	3
1207901020	10	9,7	R*	M20	10,5	17,80	230	89	120	15	35	7
1207901220	12	11,4	R*	M20	12,5	20,00	249	105	120	17	45	7
1207901624	16	19,4	R*	M24	17,0	28,00	363	160	170	25	111	3

Måltabell

