



## GN Socket CR SO4

### Produkt informasjon

**Generelt:** Certex Norge as kan levere socket GN SO4 CR i støpestål som er lakkert og galvanisert

**Materiale:** Støpestål.

**Overflate:** Lakkert/galvanisert.

**Sikkerhetsfaktor:** 5:1.

Art. nr.	Tau diameter mm	Bruddstyrke MBL	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Vekt kg	Leveringstid (dager)
122103600100	31-36	140	140	85	38	39	75	124	35	6,5	3
122104200100	38-42	160	160	110	42	44	92	130	38	8	7
122104800100	43-48	200	188	128	50	51	110	180	45	17	3
122105400100	49-54	250	215	125	55	57	115	200	50	23	7
122106000100	55-60	300	23	145	65	63	135	230	57	33	3
122106800100	61-68	400	250	160	75	73	160	265	65	50	3
122107500100	69-75	500	280	175	80	79	170	278	70	59	7
122108000100	76-80	600	315	210	85	86	184	300	75	74	3
122108600100	81-86	700	340	205	100	92	204	320	90	89	3
122109300100	87-93	800	360	220	105	99	215	340	95	104	7
122110200100	94-102	900	380	240	110	108	234	376	100	134	7
122111500100	108-115	1 000	450	260	125	120	252	400	110	180	3